

Have part of the next
applicator company

MM

8:49 AM

DC Voltage
Auto-Range

0.000 V

U	Ũ	A	Ã	Ω	🔊	⚡	+
DC Voltage	AC Voltage	DC Current	AC Current	Resistance	Buzzer file	Diode	Capacitance

Range	Hold data	Difference	Auto-Range
-------	-----------	------------	------------

IPC Tester

Power button (red)

Search button (magnifying glass)

FAR+ (yellow)

NEAR+ (yellow)

TELE+ (yellow)

WIDC- (yellow)

OPEN (yellow)

CLOSE (yellow)

Navigation buttons (blue)

ENTER (orange)

PICTURE (orange)

COM1 (red)

COM2 (red)

COM3 (red)

COM4 (red)



Please peel off this mask
after application completed

Function Tester

2016-01-01 08:49:00

My APPS



Rapid video



Rapid IP Discovery



iVMS-4500 HD



gDMSS HD Lite



VLC



EZView



XMEye



File Explorer



Settings



Theme

IPC Tester



SD/MMC
CARD
READER

VIDEO
IN

VIDEO
OUT

VIDEO
IN

VIDEO
OUT



Please peel off the mask
before application completed

Function Tester

2016-01-01 08:48:49

Tools



PoE & Power Info



DMM



DroiNotes



Data monitor



Flashlight



Calculator



Quickoffice



File Explorer



Settings



Theme

IPC Tester



RECEIVER
SENDING
RECEIVER
SENDING
RECEIVER
SENDING
RECEIVER
SENDING

LAN 1
LAN 2
LAN 3
LAN 4

Please peel off this mask
ENTER application completed

Function Tester

2016-01-01 08:48:36

Cable Tester



Cable Tester



RJ45 TDR test



File Explorer



Settings



Theme

IPC Tester



60VDC
60V~
MAX
COM GAT II VIO
600mA
MAX
FUSED
10A MAX
UN FUSED
mA

Please peel off this mask
after application completed

Function Tester

2016-01-01 08:48:25

IP Camera Test

- POE power output
- IP Discovery
- ONVIF
- IPC Test
- Network Tool
- HIK
- DH test tool
- Chrome
- File Explorer
- Settings
- Theme

IPC Tester

Control panel on the right side of the device, featuring a red power button, a green OPEN button, a magnifying glass search icon, and several directional buttons (FAR+, NEAR-, TELE+, WIDE-, OPEN, CLOSE, and a central blue D-pad). Below these are two red buttons labeled ENTER and RETURN. At the bottom right, there are four circular ports: two labeled SYSTEM MAIN and two labeled (40V MAX.) FUSE, with additional labels like [COM], [GND], [VCC], and [GND] and a warning symbol.



Please peel off this mask
after application completed

Function Tester

2016-01-01 08:48:14

CVBS & HD Camera

←

CVBS

TV OUT

CVI

AHD

TVI

SDI

File Explorer

Settings

Theme

IPC Tester





Please peel off this mask
after application completed

Function Tester

2016-01-01 08:48:14

CVBS & HD Camera



CVBS



TV OUT



CVI



AHD



TVI



SDI



File Explorer



Settings



Theme

IPC Tester

